

Arena Canyon

Intel® NUC 13 Pro – NUC13ANKi3



intel
CORE™
i3

i3

Simply NUC®

Arena Canyon i3 Slim

NUC 13 Pro – NUC13ANKi3



Top-Tier Performance for the Home and Office

Introducing Arena Canyon, the NUC 13 Pro from Intel and the latest addition to Simply NUC's 4x4 business NUC lineup. Arena Canyon offers the perfect combination of size, performance, reliability, and versatility needed to drive modern businesses. The NUC 13 Pro delivers outsized performance in its 4x4 form factor with the latest in technology, from Intel's 13th Gen Raptor Lake 1315U processor to Thunderbolt 4 and Wi-Fi 6E, delivering top-tier performance for the home and office.

Protected and Productive, 24/7

The NUC 13 Pro i3 is a feature-rich device with a plethora of I/O options, equipped with dual HDMI 2.1 ports, dual Thunderbolt 4, and four USB-A ports as standard. Further expand the functionality of your unit via the replaceable lid on both the H and K models, making Arena Canyon adaptable to your specific use case. Select Arena Canyon SKUs comes with Intel vPro technology, making it ideal for office deployments with its remote manageability and added hardware-level security features. From performing remote updates to securing your files from intrusion, the NUC 13 Pro will keep you protected and productive, 24/7.

A Clean, Seamless, and Powerful Mini PC Experience

Networking is a breeze with Arena Canyon's 2.5Gb LAN port and can be expanded to add an additional 1Gb port via the replaceable lid, allowing connection redundancy and increased networking capabilities, with the added perk of an additional USB 3.0 port. Not a fan of cables? No problem. Arena Canyon comes equipped with Wi-Fi 6E and Bluetooth 5.3, allowing you to ditch the cables to get a clean, seamless, and powerful mini PC experience.

Features

- 13th Gen Intel® Core™ i3-1315U
- Intel® UHD graphics
- 2x DDR4-3200 SO-DIMM sockets
- 1x M.2 22x80 M-key supporting PCIe x4 Gen4 NVMe
- 1x M.2 22x42 B-Key supporting PCIe x1 Gen3 NVMe or SATA SSDs
- 2x HDMI 2.1 TMDS
- 2x Thunderbolt™ 4 (Alt-DP)
- Intel® Wi-Fi 6E + Bluetooth 5.3
- 1x Intel® 2.5Gb LAN
- 3x USB 3.2 Gen 2 Type-A
- 1x USB 2.0 Type-A
- 3.5mm stereo headset jack
- VESA mount included
- Kensington lock support
- 24x7 operation
- 20V 120W power supply included
- Extended service support (1-, 3-, 5-year)



Customization

- Primary storage up to 8TB Gen4 NVMe
- Memory up to 64GB
- Replaceable lid for I/O expansion
- OS options including Windows 11, Windows IoT & Ubuntu



THINK BIG, go mini

Technical Specification

Processor	Intel® 13th Gen Core™ i3-1315U 2P+4E/8T P-Cores: up to 4.5GHz - E-Cores: up to 3.3GHz 10MB Intel® Smart Cache 15W TDP
Graphics	Intel® UHD Graphics up to 1.25GHz Up to 4x displays 2x HDMI 2.1 TMDS 2x Alt-DP 2.1 via Thunderbolt 4
Memory	Dual DDR4 SODIMMs 1.2V 64GB Max Up to 3200MHz
Storage	1x M.2 22x80 M-Key x4 PCIe supporting up to NVMe Gen4 (128GB to 8TB) 1x M.2 22x42 B-Key x1 PCIe supporting up to NVMe Gen3 (128GB to 2TB) or SATA (128GB to 2TB)
Peripherals	Intel® Wi-Fi 6E AX211 Bluetooth 5.3 1x 2.5Gb LAN (i226V) 2x Thunderbolt 4 3x USB 3.2 Gen2 Type-A 1x USB 2.0 Type-A
Chassis	117 x 112 x 37 mm Kensington lock support VESA mount included
Expansion	2x USB 2.0 header Replaceable lid
Audio	Up to 7.1 multichannel digital audio on HDMI and Thunderbolt ports 3.5mm front stereo headset jack
Power	12-20V _{DC} input range 20V _{DC} 120W power supply included
Additional Features	Delayed AC start Auto CMOS reset DC transient voltage suppression DC overvoltage/undervoltage protection Display emulation via HDMI (headless, virtual, and persistent displays)

Certifications and Regulations

Safety Regulations and Standards	IEC/EN/UL 62368-1
EMC/RF Regulations & Standards	FCC Part 15B CISPR/EN 55032/55035 ICES-003 VCCI 32 AS/NZS CISPR 32 EN 300 328 EN 301 893 EN 300 440 EN 301 489-1/17 EN 62311 AS/NZS 4268 AS/NZS 2772.2
Environmental Regulations	RoHS Compliant REACH Compliant
Certified Operating Systems	Windows 10 IoT Windows 11 64-bit (Pro, Home and IoT) Linux (Ubuntu)
Environmental Operating Temp	0°C to +40°C Ambient operating temp